

Tipping Grape Transporter TWV 50/60 including vibrating discharge

Loading volume 50/60 HL

Automatic braking system 25 km/h or Air brake system 40 km/h Grape Transporter with hydraulic tipping hopper and vibrating discharge. Hopper and vibrating discharge made of INOX 304. Steel Chassis painted [2-component finish]

Pre-dejuicing zone on vibrating discharge including juice discharge Thread DN 50.

Loading height: approx. 1650 mm
Loading lip: approx. 1880 mm
Hopper height: approx. 850 mm
Outlet width: approx. 975 mm
Trailer and Hopper width: approx. 2000 mm



Loading volume 75HL

Automatic braking system 25 km/h or Air brake system 40 km/h Grape Transporter with hydraulic tipping hopper and vibrating discharge. Hopper and vibrating discharge made of INOX 304. Steel Chassis painted [2-component finish]

Pre-dejuicing zone on vibrating discharge including juice discharge Thread DN 50.

Loading height: approx. 1800 mm
Loading lip: approx. 1980 mm
Hopper height: approx. 950 mm
Outlet width: approx. 975 mm
Trailer and Hopper width: approx. 2200 mm







Armbruster Kelterei-Technologie GmbH Zu den Weiherwiesen 1-3 74363 Güglingen

Phone: +49 7135-9506 O e-Mail: info@rotovib.eu www.rotovib.eu